

ELECTRA Series



20W ~ 60W



80W ~ 150W



200W ~ 300W








FEATURES

Application:	LED Shoe Box
LED Source:	Cree
Warranty:	5 years
Long life:	50,000+ hours at L70 standards
CRI:	>70
Working Temp:	-40°F ~ +122°F
IP Rating:	IP 65
Lab Tested:	National listing lab test in accordance with IES Standards
Solid-State:	High-Shock and High-Vibration Resistant
Instant-On:	Instant-On and Instant Re-strike

SPECIFICATIONS

Fixture Model	Wattages	Total Lumens	EPA	Dimensions (inch L x H x W)	Weight (lbs)	Certs	Beam Angle
ELECTRA-24W	24W	2730.6 lm	1.07	10.83 x 14.33 x 6.93	9.92	ETL	
ELECTRA-48W	48W	4933.3 lm	1.07	10.83 x 14.33 x 6.93	9.92	ETL	85° x 135°
ELECTRA-80W	80W	8693.8 lm	1.59	13.5 x 17.05 x 6.93	15	ETL / DLC	90° x 90°
ELECTRA-100W	100W	11202.3 lm	1.59	13.5 x 17.05 x 6.93	15	ETL / DLC	90° x 120°
ELECTRA-150W	150W	16517.2 lm	1.59	13.5 x 17.05 x 6.93	15	ETL / DLC	90° x 140°
ELECTRA-200W	200W	19500 lm	2.69	29.3 x 13.5 x 5.67	26	ETL / DLC	120° x 120°
ELECTRA-300W	300W	32336.3 lm	2.69	29.3 x 13.5 x 5.67	26	ETL / DLC	

ORDERING INFORMATION

Model	Watts	Input Voltage	Fixture Color	Photosensor	Color Temperature	Mounting	Beam Angle		
ELECTRA	300W	90-277V	BL	NO	50K	A: Slip Fitter	90° x 120°		
	24W	90 - 277V	BL: Black (RAL: 9005)	PS: Photosensor	30K: 2700K ~ 3300K	A: Slip Fitter	85° x 135°		
	48W								
	80W	480V	BR: Brown (RAL: 7022)		40K: 3700K ~ 4300K	B: Side Pole Flat	90° x 90°		
	100W								
	150W							C: Side Pole Curved	90° x 120°
	200W	300W	WH: White (RAL: 9010)	No	50K: 4700K ~ 5300K	D: Enforced Side Pole Flat	90° x 140°		
	300W								
					60K: 5700K ~ 6300K	E: Enforced Side Pole Curved	120° x 120°		
						