

AG ALL GREEN LIGHTING, INC.

NEPTUNE Series



FEATURES

Application:	Government & Municipal, Roadway, Parking Lot and High Way, etc
Source:	Driver: Meanwell HLG (IP 67) / LED: CREE Light Engine IP 66
Warranty:	5 years
Long life:	100,000+ calculated hours
Power Factor:	> 0.9
Housing:	Die cast aluminum housing with integral heat sinkfins to optimize thermal management through conductive and convective cooling, toolless entry.
Surge Protection:	Integral 10kV/10kA surge suppression protection tested in accordance with UL1449 IEEE/ANSI Category C
Lab Tested:	National listing lab test in accordance with IES Standards
Solid-State:	High-Shock and High-Vibration Resistant
Instant-On:	Instant-On and Instant Re-strike

SPECIFICATIONS

Fixture Model	EPA	MH Replacement	Dimensions (inch)	Weight (lbs)	Certs	Temperature(°F)	CRI	IP Rating
NEPTUNE-25W	0.54 ft ²	50W	18 x 10 x 4	6.6	UL / DLC			
NEPTUNE-40W	0.54 ft ²	100W	18 x 10 x 4	6.6	UL / DLC			
NEPTUNE-65W	0.54 ft ²	160W	18x 10 x 4	6.6	UL / DLC			
NEPTUNE-80W	0.54 ft ²	200W	18x 10 x 4	6.6	UL / DLC			
NEPTUNE-100W	0.54 ft ²	250W	18x 10 x 4	6.6	UL / DLC	-40°F ~ +122°F	> 0.7	IP 65
NEPTUNE-120W	0.86 ft ²	300W	22.5 x 13 x5.3	14.3	UL / DLC			
NEPTUNE-150W	0.86 ft ²	350W	22.5 x 13 x5.3	14.3	UL / DLC			
NEPTUNE-180W	0.86 ft ²	450W	22.5 x 13 x5.3	14.3	UL / DLC			
NEPTUNE-240W	0.86 ft ²	600W	22.5 x 13 x5.3	14.3	UL / DLC			

LUMEN MAINTENANCE FACTOR

Data references the extrapolated performance projection for the platforms noted in 77F ambient temperature, based on 10,000 hours of LED testing (tested per IESNA LM-80-08 and projected per IESNA TM-21-11). To calculate LLF, use the lumen maintenance factor that corresponds to the desired number of operating hours below:

Operating Hours	0	25,000	50,000	75,000	100,000
NEPTUNE-25W	1	0.92	0.85	0.8	0.75
NEPTUNE-100W	1	0.91	0.85	0.79	0.73
NEPTUNE-150W	1	0.92	0.85	0.8	0.75
NEPTUNE-240W	1	0.91	0.85	0.79	0.73

TOTAL LUMENS (LM)

	Type II		Type III		Type V	
	40K	57K	40K	57K	40K	57K
NEPTUNE-25W	2,825	3201	2,866	3,225	2,823	2,906
NEPTUNE-40W	4,853	5260	4,706	4,706	4,745	4,932
NEPTUNE-65W	7,401	7622	6,889	6,889	6,684	6,962
NEPTUNE-80W	9,275	10161	9,407	9,407	8,951	9,312
NEPTUNE-100W	11,636	11564	10,813	10,813	10,075	10,788
NEPTUNE-120W	13169	13,779	13,250	13,250	13,748	14,182
NEPTUNE-150W	16,987	18446	17,439	17,439	17,148	18,494
NEPTUNE-180W	18,543	19801	17,990	17,990	18,493	19,947
NEPTUNE-240W	24,376	26375	24,838	24,838	24,473	26,806

ISO-FOOTCANDLE CHART

	NEPTUNE-100W	NEPTUNE-150W	NEPTUNE-240W																																																																																			
<p>illuminance at a Distance</p> <p>Center Beam LUX</p> <table border="1"> <thead> <tr> <th>Distance</th> <th>Center Beam LUX</th> <th>Beam Width V</th> <th>Beam Width H</th> </tr> </thead> <tbody> <tr><td>2m</td><td>453.42 LUX</td><td>1.0m</td><td>3.1m</td></tr> <tr><td>4m</td><td>113.35 LUX</td><td>1.9m</td><td>6.1m</td></tr> <tr><td>6m</td><td>50.38 LUX</td><td>2.9m</td><td>9.2m</td></tr> <tr><td>8m</td><td>28.34 LUX</td><td>3.9m</td><td>12.3m</td></tr> <tr><td>10m</td><td>18.14 LUX</td><td>4.8m</td><td>15.3m</td></tr> <tr><td>12m</td><td>12.59 LUX</td><td>5.8m</td><td>18.4m</td></tr> </tbody> </table> <p>Vert. Spread 27.1 Horiz. Spread 74.9</p>	Distance	Center Beam LUX	Beam Width V	Beam Width H	2m	453.42 LUX	1.0m	3.1m	4m	113.35 LUX	1.9m	6.1m	6m	50.38 LUX	2.9m	9.2m	8m	28.34 LUX	3.9m	12.3m	10m	18.14 LUX	4.8m	15.3m	12m	12.59 LUX	5.8m	18.4m	<p>illuminance at a Distance</p> <p>Center Beam LUX</p> <table border="1"> <thead> <tr> <th>Distance</th> <th>Center Beam LUX</th> <th>Beam Width V</th> <th>Beam Width H</th> </tr> </thead> <tbody> <tr><td>2m</td><td>713.45 LUX</td><td>0.9m</td><td>3.5m</td></tr> <tr><td>4m</td><td>178.36 LUX</td><td>1.9m</td><td>7.0m</td></tr> <tr><td>6m</td><td>79.27 LUX</td><td>2.8m</td><td>10.4m</td></tr> <tr><td>8m</td><td>44.59 LUX</td><td>3.7m</td><td>13.9m</td></tr> <tr><td>10m</td><td>28.54 LUX</td><td>4.7m</td><td>17.4m</td></tr> <tr><td>12m</td><td>19.82 LUX</td><td>5.6m</td><td>20.9m</td></tr> </tbody> </table> <p>Vert. Spread 26.3 Horiz. Spread 82.0</p>	Distance	Center Beam LUX	Beam Width V	Beam Width H	2m	713.45 LUX	0.9m	3.5m	4m	178.36 LUX	1.9m	7.0m	6m	79.27 LUX	2.8m	10.4m	8m	44.59 LUX	3.7m	13.9m	10m	28.54 LUX	4.7m	17.4m	12m	19.82 LUX	5.6m	20.9m	<p>illuminance at a Distance</p> <p>Center Beam LUX</p> <table border="1"> <thead> <tr> <th>Distance</th> <th>Center Beam LUX</th> <th>Beam Width V</th> <th>Beam Width H</th> </tr> </thead> <tbody> <tr><td>2m</td><td>1115.16 LUX</td><td>1.0m</td><td>3.3m</td></tr> <tr><td>4m</td><td>278.79 LUX</td><td>1.9m</td><td>6.5m</td></tr> <tr><td>6m</td><td>123.91 LUX</td><td>2.9m</td><td>9.8m</td></tr> <tr><td>8m</td><td>69.70 LUX</td><td>3.9m</td><td>13.1m</td></tr> <tr><td>10m</td><td>44.61 LUX</td><td>4.9m</td><td>16.3m</td></tr> <tr><td>12m</td><td>30.98 LUX</td><td>5.8m</td><td>19.6m</td></tr> </tbody> </table> <p>Vert. Spread 27.3 Horiz. Spread 78.6</p>	Distance	Center Beam LUX	Beam Width V	Beam Width H	2m	1115.16 LUX	1.0m	3.3m	4m	278.79 LUX	1.9m	6.5m	6m	123.91 LUX	2.9m	9.8m	8m	69.70 LUX	3.9m	13.1m	10m	44.61 LUX	4.9m	16.3m	12m	30.98 LUX	5.8m	19.6m
Distance	Center Beam LUX	Beam Width V	Beam Width H																																																																																			
2m	453.42 LUX	1.0m	3.1m																																																																																			
4m	113.35 LUX	1.9m	6.1m																																																																																			
6m	50.38 LUX	2.9m	9.2m																																																																																			
8m	28.34 LUX	3.9m	12.3m																																																																																			
10m	18.14 LUX	4.8m	15.3m																																																																																			
12m	12.59 LUX	5.8m	18.4m																																																																																			
Distance	Center Beam LUX	Beam Width V	Beam Width H																																																																																			
2m	713.45 LUX	0.9m	3.5m																																																																																			
4m	178.36 LUX	1.9m	7.0m																																																																																			
6m	79.27 LUX	2.8m	10.4m																																																																																			
8m	44.59 LUX	3.7m	13.9m																																																																																			
10m	28.54 LUX	4.7m	17.4m																																																																																			
12m	19.82 LUX	5.6m	20.9m																																																																																			
Distance	Center Beam LUX	Beam Width V	Beam Width H																																																																																			
2m	1115.16 LUX	1.0m	3.3m																																																																																			
4m	278.79 LUX	1.9m	6.5m																																																																																			
6m	123.91 LUX	2.9m	9.8m																																																																																			
8m	69.70 LUX	3.9m	13.1m																																																																																			
10m	44.61 LUX	4.9m	16.3m																																																																																			
12m	30.98 LUX	5.8m	19.6m																																																																																			

ORDERING INFORMATION

Model	Wattage	Input Voltage	Fixture Color	CCT	PC	Dimming	Motion Sensor	Beam Angle
NEPTUNE	25W	100-277V	GR	50K	7PC - SC	DM	MS	T5
	25W	100-277V			3PC: 3-Pin Photocell	DM:	MS: Motion	Type II
	40W	100-277V with photo electric switch	GR: Grey (RAL: 7038)	30K: 27K~33K	5PC: 5-Pin Photocell	Dimmable	Sensor	Type III
	65W				7PC: 7-Pin Photocell	ND: None	NM: None	Type V
	80W	347-480V	BL: Black (RAL:9017)	40K: 37K~43K	SC: Shorting Cap			
	100W							
	120W		BR: Bronze (RAL:8028)	50K: 47K~53K				
	150W							
	180W		Custom Colors Available	60K 57K~63K				
	240W							